

Certificate of Compliance

Certificate: 1748096 (LR 105802) **Master Contract:** 162767

Project: 2508314 **Date Issued:** April 12, 2012

Issued to: KROHNE, Inc.

7 Dearborn Rd Peabody, MA 01960

USA

Attention: Rick Loiselle

The products listed below are eligible to bear the CSA Mark shown



Joe da Sílva

Issued by: Joe da Silva, C.E.T.

PRODUCTS

CLASS 2258 02 - PROCESS CONTROL EQUIPMENT - For Hazardous Locations

Class I, Gps. A, B, C and D; Cl. II, Gps. E, F and G; Cl. III:

Class I, Div. 2, Gps. A, B, C and D; Cl. II, Div. 2, F and G; Cl. III, Div. 2:

Variable area flowmeter Series H250a/ b /M10 consisting of H250 or H250C flowtube and M10 converter, rated input 24 ±30% Vdc, 4 –20 mA, operating ambient –40°C to 60°C; Encl. Type 4X and 6; MWP 4,960 psi.,

APPLICABLE REQUIREMENTS

CAN/CSA C22.2 No. 0-M91 (R2001) - General Requirements - Canadian Electrical Code, Part II

CSA Std C22.2 No. 25-1966 - Enclosures for Use in Class II, Groups E, F and G Hazardous Locations

CSA Std C22.2 No. 30-M1986 - Explosion-Proof Enclosures for Use in Class I Hazardous Locations

CSA C22.2 No. 94-M91 (R2001) - Special Purpose Enclosures; Industrial Products

CSA Std C22.2 No. 142-M1987 - Process Control Equipment

CSA Std C22.2 No. 213-M1987 - Non-Incendive Electrical Equipment for Use in Class I, Division 2 Hazardous Locations

MARKINGS

DQD 507 Rev. 2009-09-01 Page: 1



Certificate: 1748096 (LR 105802) **Master Contract:** 162767

Project: 2508314 **Date Issued:** April 12, 2012

- Submittor's Name

- Model Number
- Serial Number
- Electrical Rating
- Maxmium Operating Pressure
- Operating Ambient
- Enclosure Type
- Hazardous Location Designation (Including the use of Zone designation)
- Warning Regarding Removing Cover While Circuits Are Alive

DQD 507 Rev. 2009-09-01 Page: 2