

The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Thursday**, **March 21**, **2019** at 12:15 a.m. Eastern Time. Please <u>contact NSF</u> to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: <u>http://info.nsf.org/Certified/PwsComponents/Listings.asp?</u> <u>Company=0K810&Standard=061&</u>

NSF/ANSI 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of <u>Abbreviations used in these Listings</u>. Click here for the definitions of <u>Water Contact Temperatures denoted in these Listings</u>.

Krohne Altometer Kerkeplaat 12 Dordrecht 3313 LC The Netherlands 31 786306300 Visit this company's website (http://www.krohne.com)

Facility : Dordrecht, The Netherlands

Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
	Siec	Temp	
Water Meters[1]			
Optiflux 2000 F[2] [G]	[4]	CLD 23	MLTPL
Optiflux 2000 F[3] [G]	[5]	CLD 23	MLTPL
Optiflux 2010 C[2] [G]	[4]	CLD 23	MLTPL
Optiflux 2010 C[3] [G]	[5]	CLD 23	MLTPL
Optiflux 2050 C[2] [G]	[4]	CLD 23	MLTPL
Optiflux 2050 C[3] [G]	[5]	CLD 23	MLTPL
Optiflux 2100 C[2] [G]	[4]	CLD 23	MLTPL
Optiflux 2100 C[3] [G]	[5]	CLD 23	MLTPL
Optiflux 2300 C[2] [G]	[4]	CLD 23	MLTPL
Optiflux 2300 C[3] [G]	[5]	CLD 23	MLTPL
Waterflux 3000 F (IP68)*[7] [G]	[6]	CLD 23	MLTPL
Waterflux 3000 F*[7] [G]	[6]	CLD 23	MLTPL
Waterflux 3050 C[G]	[6]	CLD 23	MLTPL
Waterflux 3070 C (IP68)*[7] [G]	[6]	CLD 23	MLTPL

Waterflux 3070 C*[7] [G]	[6]	CLD 23	MLTPL
Waterflux 3100 C[G]	[6]	CLD 23	MLTPL
Waterflux 3300 C[G]	[6]	CLD 23	MLTPL

- Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.
- [2] Certified product contains Hastelloy C-22, Hastelloy C-4, or Stainless Steel 1.4571 electrodes and a hard rubber liner.
- [3] Certified product contains Hastelloy C-22, Hastelloy C-4, or Stainless Steel 1.4571 electrodes and a polypropylene liner.
- [4] DN25 DN3000/1" 120"
- [5] DN25 DN150/1" 6"
- [6] DN25 DN 600/1" 24"
- [7] * Option PT-Sensor possible
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Number of matching Manufacturers is 1 Number of matching Products is 17 Processing time was 0 seconds